

Anhydride- Cont'd

Series 3500

3000 psi (24.1 MPa)

Pipe Size		Thread Type	Pipe Dimensions								Connection Diameter		Minimum Bending Radius		Short-Term Tensile Rating		Mfg. Loc.*
			Inside Diameter		Outside Diameter		Nominal Wall Thickness		Pipe Weight								
in	mm		in	mm	in	mm	in	mm	lbs/ft	kg/m	in	mm	ft	m	lbs	kgs	
6	150	SS HP	5.85	148.6	7.32	186.0	0.74	18.7	14.43	21.5	9.74	247.4	369	112.5	45100	13746	W

Aliphatic Amine

Series 500

500 psi (3.4 MPa) @ 150°F (65.6°C), 450 psi (3.4 MPa) @ 180°F (82.2°C), 400 psi (2.8 MPa) @ 200°F (93.3°C)

Pipe Size		Thread Type	Pipe Dimensions								Connection Diameter		Minimum Bending Radius		Short-Term Tensile Rating		Mfg. Loc.*
			Inside Diameter		Outside Diameter		Nominal Wall Thickness		Pipe Weight								
in	mm		in	mm	in	mm	in	mm	lbs/ft	kg/m	in	mm	ft	m	lbs	kgs	
8	200	SS	7.74	196.6	8.01	203.5	0.14	3.6	3.6	5.4	9.39	238.5	401	122.2	9600	4355	S
10	250	SS	9.84	249.9	10.2	259.1	0.18	4.6	6.7	10.0	12.1	307.3	510	155.4	15900	7212	S
12	300	SS	11.81	300	12.23	310.6	0.21	5.3	8.7	12.9	14.1	358.1	611	186.2	22400	10161	S

Series 800

800 psi (5.5 MPa) @ 150°F (65.6°C), 700 psi (4.8 MPa) @ 180°F (82.2°C), 650 psi (4.5 MPa) @ 200°F (93.3°C)

Pipe Size		Thread Type	Pipe Dimensions								Connection Diameter		Minimum Bending Radius		Short-Term Tensile Rating		Mfg. Loc.*
			Inside Diameter		Outside Diameter		Nominal Wall Thickness		Pipe Weight								
in	mm		in	mm	in	mm	in	mm	lbs/ft	kg/m	in	mm	ft	m	lbs	kgs	
8	200	SS	7.74	196.6	8.18	207.8	0.22	5.6	5.5	8.2	9.63	244.6	409	124.7	15600	7076	S
10	250	SS	9.84	249.9	10.41	264.4	0.28	7.1	9.8	14.6	12.35	313.7	520	158.5	25600	11612	S
12	300	SS	11.81	300	12.48	317	0.33	8.4	12.6	18.7	14.4	365.8	624	190.2	36100	16375	S

Series 1000

1000 psi (6.9 MPa) @ 150°F (65.6°C), 900 psi (6.2 MPa) @ 180°F (82.2°C), 850 psi (5.9 MPa) @ 200°F (93.3°C)

Pipe Size		Thread Type	Pipe Dimensions								Connection Diameter		Minimum Bending Radius		Short-Term Tensile Rating		Mfg. Loc.*
			Inside Diameter		Outside Diameter		Nominal Wall Thickness		Pipe Weight								
in	mm		in	mm	in	mm	in	mm	lbs/ft	kg/m	in	mm	ft	m	lbs	kgs	
8	200	SS	7.74	196.6	8.29	210.6	0.28	7.1	6.9	10.3	9.79	248.7	415	126.5	19900	9027	S
10	250	SS	9.84	249.9	10.56	268.2	0.36	9.1	11.9	17.7	12.5	317.5	528	160.9	32500	14742	S
12	300	SS	11.81	300	12.65	321.3	0.42	10.7	15.4	22.9	14.7	373.4	633	192.9	45800	20775	S

Series 1250

1250 psi (8.6 MPa) @ 150°F (65.6°C), 1100 psi (7.6 MPa) @ 180°F (82.2°C) 1050 psi (7.2 MPa) @ 200°F (93.3°C)

Pipe Size		Thread Type	Pipe Dimensions								Connection Diameter		Minimum Bending Radius		Short-Term Tensile Rating		Mfg. Loc.*
			Inside Diameter		Outside Diameter		Nominal Wall Thickness		Pipe Weight								
in	mm		in	mm	in	mm	in	mm	lbs/ft	kg/m	in	mm	ft	m	lbs	kgs	
8	200	SS	7.74	196.6	8.45	214.6	0.36	9.1	8.6	12.8	10	254	422	128.6	25700	11658	S
10	250	SS	9.84	249.9	10.74	272.8	0.45	11.4	14.6	21.7	12.8	325.1	537	163.7	41400	18779	S
12	300	SS	11.81	300	12.86	326.6	0.53	13.5	19.2	28.6	15	381	643	196	57800	26218	S