



INSTRUMENT & CONTROL LEGEND

ITEM	DESCRIPTION	LOCATION
LV-1	LLINC MODEL PT2265G-29	V-1
LV-2	LLINC MODEL PT2265G-03	V-2
LV-3	LLINC MODEL PT2265G-01	V-3
LV-4	LLINC MODEL PT2265G-01	REBOILER
LV-5	FISHER 125 POC 2" x 3/8"	V-1
LV-6	FISHER 512 RB 1 1/2 x 1/2"	V-2
LV-7	FISHER 512 RB 1 1/2 x 1/2"	V-3
LV-8	FISHER 126 POC 1" x 3/8"	REBOILER
RV-1/9	TAYLOR 1" x 1/2" SET @ 1000#	V-1 & V-9
RV-2	TAYLOR 1" x 1/2" SET @ 400#	TOWER
RV-3/8	TAYLOR 1/2" x 1/2" SET @ 150#	V-2 & V-8
RV-4	TAYLOR 1/2" x 1/2" SET @ 150#	GLY. FILTER
RV-5	TAYLOR 1" x 1/2" SET @ 300#	V-4
RV-6	TAYLOR 1" x 1/2" SET @ 300#	COMP.
RV-7	TAYLOR 1" x 1/2" SET @ 300#	COMP.
RV-8	FISHER 126 POC 1" x 3/8"	TOWER/REH.
TC-1	JOHNSON V-4329-1008 V/V-30004 9-13 3/8"	REBOILER
TC-2	KIMRAY 112 SMT DAB	H-1
TC-3	FISHER 512 RB 1 1/2 x 3/4"	H-1
TC-4	TAYLOR 442	REBOILER
TC-5	KIMRAY T-12	H-1
PC-1	FISHER 620, 1" x 1/2" W/ 40-100" SPRING	V-3
PC-2	FISHER 620	H-1
PC-3	FISHER 620, 1" x 1/2" W/ 40-100" SPRING	H-1
PC-4	FISHER 620, 1" x 1/2" W/ 40-100" SPRING	COMP.
PC-5	FISHER 4150, 10-500"	TOWER
PC-6	PRC CONTROLLER 101, JOHNSON 8575	H-1
PC-7/2	MURPHY VS-2	COMP. COND
PC-8/1	FCI, 12-64-4 (OPTIONAL)	V-1
PC-8/2	FCI, 12-64-4	H-1
PC-8/3	MURPHY OPL-250	H-1
PC-8/4	LLINC 471-01 (OPTIONAL)	V-3
PC-8/5	LLINC 471-01	TOWER
PC-9/1	MURPHY OPL-400	COMP.
PC-9/2	MURPHY OPL-30V-200	COMP.
PC-9/3	MURPHY O-100 COMP. OIL PRESS	COMP.
PC-9/4	MURPHY O-500 COMP. DISCH. THERM.	COMP.
PC-10	LLINC MODEL PT2265G-1-01	V-2
PC-11	FISHER 512 RB 1 1/2 x 1/2"	V-3
PC-12	FISHER 538 25-75" SPRING	V-3
PC-13	FISHER 126 POC 1" x 3/8"	V-4
PC-14	LLINC 471-01	V-4, V-6
PC-15	TY BARTON 380	V-8
PC-16	LLINC 471-01	H
PC-17	LLINC MODEL PT2265G-03	V-3

INSULATION:
HOT: CALCIUM SILICATE
COLD: URETHANE
PIPING: URETHANE

COMPRESSOR:
ARIEL: 16 P, 2 W/ ONE 1 1/2" M. CYL, ONE 3/4" M. CYL.
ELECTRIC NO-FLAME SWITCH (VENCO)

MOTORS:
100 HP ELECTRIC W/ REDUCED VOLTAGE STARTER, 24" 440V, 1500 RPM

DRIVE COUPLING:
DOUBLE FLEXING DISC COUPLING TYP
AKEM 312

PROCESS EQUIPMENT CORPORATION
SHELDON, WYOMING

DWG	REFERENCE